

## Long Answer Type Questions [4 marks each]

### Question 1:

Define member function delque() to perform delete operation on a linked queue where each node has the following structure :

```
struct node
{
char name[20]
int marks;
node *link;
};
class queue
{
node *front,`rear;
public :
queue() {front=rear=NULL;
}
void delque ( );
}; [CBSE Comptt., 2014]
```

### Answer:

```
void queue : : delque ()
{
if ( front != NULL)
{
node *Temp = front;
cout << Temp -> name << Temp
->marks;
front = front->link;
delete Temp;
if(front == NULL)
rear = NULL;
}
else
cout << "Queue is empty";
}
```

**(4 marks for correct program)**

### Question 2:

Give the necessary declaration of linked' implemented Queue containing players information (as defined in the following definition of Node). Also write a user defined function in C++ to delete one Player's information from the Queue.

**[CBSE Comptt., 2013]**

```
struct node
{
    int Player No ;
    char PlayerName[20];
    Node*Link;
}
```

**Answer:**

```
NODE *QUEUEDEL(Node * front, int val, char val2[ ])
```

```
{
    Node *temp;
    if (front ==NULL)    [1]
        cout<<"Queue EMPTY";
    {
        else
        {
            temp=front ;
            temp->PlayerNo=val;    [1]
            strcpy (temp->PlayerName, val2);
            front=front->Link;    [1]
            delete temp;
        }
        return (front);
    } [1]
```

**Question 3:**

Write a function QDELETE ( ) in C++ to perform delete operation on a Linked Queue, which contains Passenger no and Passenger name. Consider the following definition of Node in the code,

```
struct node
{
    long int Pno;
    char Pname [20];
    node *Link;
}; [O.D, 2013]
```

**Answer:**

```
//Function to delete queue elements Node * QUEUE (Node * front, int val, char val [ ])
```

```
{
    Node *temp;
```

```

if (front == NULL)
cout <<"Queue Empty";
else
{
temp = front;
temp@Pno=val;
strcpy (temp@Pname, vail);
front = front@Link;
delete temp;
}
return (front);
} [4]

```

#### Question 4:

Write a function QINSERT() in C++ to perform insert operation on a Linked Queue, which contains Client no and Client name. Consider the following definition of NODE in the code of . QINSERT (). **[Delhi, 2013]**

```

struct Node
{
long int Cno; // Client No
char Cname [20]; //
Client Name
Node *Next ;
};

```

#### Answer:

Function to Insert element

```
Node * QINSERT (Node *rear, int val),
```

```

char val []
{
Node *temp;
temp = new Node;
temp@Cno = val;
strcpy (temp@Cname, val);
temp@NEXT=NULL;
rear@NEXT=temp;
rear=temp;
return (rear);
} [4]

```

#### Question 5:

Write a function in C++ to perform Insert operation in a circular Queue containing Layer's information (represented with the help of an array of structure Player).  
**[CBSE SQP 2013]**

```
struct Player
{
    long PID;    //Player ID
    char Pname [20];}    //Player Name
    Player*Link;
}
```

**Answer:**

```
void Insert ( )
{
    PLAYER *P = new PLAYER;
    cout <<"Enter Player ID & Name";
    cin>>P→PID;
    gets (P→ Pname);
    P→Link=NULL;
    if ((fronts = NULL) && (rear == NULL))
    {
        front = rear = P;
    }
    else
    {
        rear→Link = P;
        rear = P;
    }
}    [4]
```

**Question 6:**

Write a function in C++ to perform insert operation in a static circular queue containing book's information (represented with the help of an array of structure BOOK). **[O.D, 2012]**

```
struct BOOK
{
    long Accno; //Book Accession Number char Title[20];    //Book Title
};
```

**Answer:**

```
struct BOOK
{
    long Accno; char Title [20] ;
    int front, rear;
}B [10] ;
```

```

void insert()
{
if (r e a r == s i z e - 1 & & f r o n t == 0 || front == rear+1)
{
cout<<"\n Circular queue is full"; return;
}
else if(rear== -1)
{
rear++;
front++;
}
else if(rear==size-1)
rear=0;
else
{
rear++;
}
cout<<"Enter Title : " ;
cin>>B[rear] . Title;
cout<<"Enter Accno : " ;
cin>>B[rear] . Accno;
}    [4]

```

#### Question 7:

Write a function in C++ to perform insert operation in a dynamic queue containing DVD's information (represented with the help of an array of structure DVD). **[Delhi, 2012]**

#### Answer:

*/\*Function in C++ to perform insert in a dynamic queue is given as\*/*

```

struct DVD
{
long No; // DVD Number
char Title[20]; // DVD Title
DVD *Link
};
void insert(struct DVD *start, char data[20] ) ;
{
DVD *q, *temp;
// Dynamic memory has been allocated for a node
temp=(DVD*)malloc(size of (DVD));
temp=Title[20]=data[20] ;
temp"Next=NULL;
if (start  =  = NULL) /*Element
inserted at end*/

```

```

while (q->Next != NULL)
q=q->Next;
q->Next = temp;
} [4]

```

#### Question 8:

Write the definition of a member function INSERT() for a class QUEUE in C++, to insert a CUSTOMER in a dynamically allocated Queue of items considering the following code which is already written as a part of the program,

```

struct CUSTOMER
{
int CNO; char CNAME[20];
CUSTOMER *Link;
};
Class QUEUE
{
CUSTOMER *R,*F;
Public:
QUEUE(){R=NULL;F=NULL;}
void INSERT();
void DELETE()
~QUEUE();
}; [CBSE SQP 2013]

```

#### Answer:

```

void QUEUE : : INSERT ()
{
CUSTOMER*T=new CUSTOMER;
cin>>T>>;
gets(T->CNAME);
//OR cin>>T>>CNAME;
T->LINK = NULL;
if (R==NULL)
{
F=T; R=T;
}
else
{ R->LINK = T; R = T;
}
}

```

**(1 Mark for correct a new code)**

**(1/2 Mark for entering data to new code)**

(1/2 Mark for assigning NULL to link of the new code)

(1/2 Mark for assigning front to the first code as  $L=T$ )

(1/2 Mark for linking the last node to new code as  $R \rightarrow \text{Link}=T$ )

(1 Mark for assign Read to the new code as  $R=T$ )